

Wireless Microphone EUDAC AUDIO SKM-600



Technical Specifications

Receiver SKM-600

Frequency Range	640 MHz – 690 MHz
Oscillation Mode	Phase-Locked Loop (PLL)
Frequency Stability	$\pm 0.0005\%$
Sensitivity	6 dB μ V at 25 KHz deviation, S/N > 60 dB
Max Deviation	± 45 kHz
Bandwidth	50 MHz
S/N Ratio	> 108 dB
Total Harmonic Distortion (THD)	< 0.4% @ 1 kHz
Frequency Response	60 Hz ~ 18 kHz ± 3 dB
Max Output Voltage	Balanced: -20 dBV / 100 Ω
Power Supply	AC 100 – 240V, 50/60 Hz, 10W
Weight	4.3 kg
Dimensions (mm)	421 (L) $\times$ 43 (H) $\times$ 206 (W)
Transmission Distance	200 m

Handheld Microphone SKM-600

Frequency Range	640 MHz - 690 MHz
Radiation	<-63 dBm
Bandwidth	80 MHz
Max Deviation	± 45 kHz
Output Power	30 mW
Frequency Response	50 Hz ~ 18 kHz
Max Sound Pressure Level	130 dB SPL
RF Output Power	8 mW; 8 mW / 15 mW (selectable)
Battery	2 × AA
Battery Life	~ 6 hours
Dimensions (mm)	265 mm (length) × 56 mm (diameter)
Reception Distance	200 m ²

SKU: EUDAC-SKM-600. Category: Microphone.